



## 12004PFXAB EPIC™ AMAZING BASE

WILFLEX™ Epic Amazing Base is a non-phthalate mixing base for manual and automatic screen printing on 100% cotton and cotton/poly blend substrates. Combining elements in design versatility and press performance, Amazing Base has been engineered to produce optimal color vibrancy and printability providing the versatility and performance you expect from a Wilflex Color System.

### HIGHLIGHTS

- Clean, bright colors when mixed with Wilflex™ PCs or Equalizers
- Wet-on-wet printing at high production speeds with exceptional resistance to build-up
- Semi-opaque colors
- Satin finish
- Good color fastness to crocking test

### PRINTING TIPS

- Use consistent, high-tensioned screen mesh and sharp edged squeegees for best print results
- When blended according to formulations, colors will be semi-opaque
- Exhibits good color reproduction on white garment and over a base plate. For some colors, base mixing systems are limited in color saturation and may require an increased ink deposit or formula adjustment to achieve accurate color
- Amazing Base is not a low-bleed ink; when printing on fabrics that are prone to bleed underbase with an approved WILFLEX low bleed white and/or blocker
- Exhibits good color retention in high-speed wet-on-wet production with exceptional resistance to build up
- Adjust flash cure temperature and dwell time so ink is just dry to touch. Depending on flash unit, a 2 - 3 second flash is adequate
- For cold-peel transfers, use a coated release paper or polyester film

### COMPLIANCE

- Non-phthalate
- For individual compliance certifications and conformity statements, please visit [www.avient.com/wilflex-compliance](http://www.avient.com/wilflex-compliance)

### PRECAUTIONS

The information above is given in good faith and does not release you from testing inks and fabrics to confirm suitability of substrate and application process to meet your customer standards and specifications




AVIENT  
SPECIALTY  
INKS

V1.00 (Modified: 11/30/2020)

## PRODUCT INFORMATION BULLETIN



### RECOMMENDED PARAMETERS



#### Fabric Types

100% cotton, cotton/poly blends, some synthetics



#### Mesh

Count: 86-305 t/in (34-120 t/cm)  
Tension: 25-35 n/cm<sup>2</sup>



#### Squeegee

60/90/60, 70/90/70, 60-90  
Profile: Square, Sharp  
Stroke: Medium flood, Medium-Fast stroke  
Angle: 10-15%



#### Stencil

2 over 2  
Off Contact: 1/16" (.2cm)  
Emulsion Over Mesh: 15-20%



#### Flash & Cure

Flash: 220°F (105°C)  
Cure: 300°F (149°C)



#### Pigment Loading



#### Wilflex™ Additives

Epic Viscosity Buster-1% max  
Epic Finesse Base



#### Storage

65-90°F (18-32°C)  
Avoid direct sunlight  
Use within one year of receipt



#### Clean Up

Ink degradant or press wash



#### Health & Safety

SDS: [www.avient.com/resources/safety-data-sheets](http://www.avient.com/resources/safety-data-sheets)  
Contact your local CSR