

Rutland™ M3 Finished Ink Mixing System Color Card

The Rutland™ M3 mixing system provides screen printers with finished inks to create custom colors. Finished inks as part of a mixing system are more forgiving than a pigment concentrate-based system, as they do not require the same level of precision of measure, or bases and additives to complete a formula.

Rutland M3 inks are very opaque, offering excellent coverage on light and dark garments alike. The low-

tack formula allows the inks to print onto 100% cotton through a range of mesh counts. It is an excellent color matching system for printing onto cotton/polyester blends when used with an added underbase with a low-bleed white or similar first-down product. Inks are formulated to prevent build-up to ensure high print efficiencies without requiring downtime to clean screens.

Pantone® Certified

Mix thousands of finished ink colors by choosing Pantone[®] colors from our IMS3.0 software

Reduced Build-Up

M3 formulations ensure high print efficiencies without the need for down time for wiping screens

Versatile Printing

Print onto 100% cotton, blends, and poly blends (blends and poly blends might require a bleed blocker underbase)

Vibrant Colors

Set of bright and very opaque colors helps printers achieve the stand-out color



This system is created for use with IMS3.0, a proprietary color formulation software from Avient Specialty Inks. Offering tools for color creation and standardizing, IMS3.0 manages daily maneuvers in a highly functional ink room by providing color management and communication agility.

Mix thousands of finished ink colors using the eight standard colors and four fluorescent colors by choosing from Pantone® colors in the IMS3.0 Mixing Software.



1.844.4AVIENT www.avient.com



Copyright © 2023, Avient Corporation. Avient makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Avient makes no warranties or guarantees respecting suitability of either Avient's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. AVIENT MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.