

INSPIRED HUES

QCM™ STANDARD COLOR CARD

QCM™ offers a wide range of high-opacity screen printing inks created to set printers up for success.

XOLB

QCM XOLB inks are low bleed, high-opacity, multi-purpose inks designed to produce extremely opaque prints, yet are very easy to print on a manual press. The smooth, creamy consistency leaves an even, uniform print on white flash bases. These inks may print opaquely on black substrates without a white surface, and can contain clean, bright pigments. Fast flash speeds allow for shorter dwell times and faster production output to increase efficiencies.

WOW

QCM WOW is a non-phthalate, high-opacity, low build-up ink line developed specifically for wet-on-wet printing. These inks are ideal for high-volume print jobs, allowing for longer press runs, fewer interruptions, minimal screen blockage, fewer misprints, and reduced need for cleaning. These are opaque inks that produce clean, brilliant colors.



To view color information for each ink, download this card and hover over the ink swatch to reveal PMS codes.

Yellow
WOW-201
XOLB-201

Gold
WOW-202
XOLB-202

Vegas Gold
WOW-205
XOLB-205

Chrome Yellow
WOW-210
XOLB-210

Orange
WOW-302
XOLB-302

Scarlet
WOW-401
XOLB-401

Fluo Pink
XOLB-404

Brite Red
WOW-408
XOLB-408

Fuchsia
WOW-453
XOLB-453

Royal Blue
WOW-503
XOLB-503

Navy Blue
WOW-504
XOLB-504

Opaque Process Blue
WOW-505
XOLB-505

Aqua Marine
XOLB-507

Star Light Royal
WOW-5104

Purple
WOW-602
XOLB-602

Maroon
XOLB-608

Kelly Green
WOW-703
XOLB-703

Lime Green
XOLB-705

Forest Green
WOW-710
XOLB-710

Grey
WOW-902
XOLB-902



Black inks are also available:

LFP-901 Black
WOW-901 Black

Color Chips: The color chips presented on this color card are simulations of QCM colors. Slight variations may be seen between these chips and actual QCM inks. Printed results may vary based on production methods such as ink film thickness, opacity, and substrate.

For more information, visit qcminks.com.

www.avient.com



Copyright © 2023, Avient Corporation. Avient makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Avient makes no warranties or guarantees respecting suitability of either Avient's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. AVIENT MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.