



Wilflex™ Revive™ Bio Plastisol™ White

Wilflex™ Revive™ Bio Plastisol™ inks are created with bio derived materials to promote the preservation of natural resources and help printers achieve their sustainability goals. Products in the Wilflex Revive range perform in the same way as a standard plastisol so no additional training is required.

HIGHLIGHTS

- Opaque Cotton White
- Performs like a plastisol in the screen, on press and on the garment
- Make your screen printing instantly sustainable
- Excellent wash durability
- Bio Plastisol™ produced from bio renewable resources
- Bio Content certified to ASTM 6866

PRINTING TIPS

- The use of Wilflex Epic Armor Black/Gray or Epic UBG is highly recommended to help protect against bleeding
- Stir inks before printing
- Preheat pallets to 150-160F/65-71C to assist with gelling
- Use consistent, high-tensioned screen mesh and sharp edged squeegees for best print results
- Easy screen clearance even on high mesh counts
- Use hard flood and low-medium squeegee pressure
- For cold-peel and hot-peel transfers,

COMPLIANCE

- Non-phthalate
- For individual compliance certifications and conformity statements, please visit: www.avient.com/wilflex-compliance

SUSTAINABILITY



Biopolymers

PRECAUTIONS

The information above is given in good faith and does not release you from testing inks and fabrics to confirm suitability of substrate and application process to meet your customer standards and specifications

PRODUCT INFORMATION BULLETIN



RECOMMENDED PARAMETERS

Fabric Types

Cotton



Mesh

Count: 86-305 t/in (34-120 t/cm)
Tension: 25-35 n/cm2



Squeegee

Durometer: 60/90/60, 70/90/70, 60-70
Profile: Square, Sharp
Stroke: Hard flood, Fast stroke
Angle: 10-15%



Stencil

2 over 2
Off Contact: 1/16" (2mm)
Emulsion Over Mesh: 15-20%



Flash & Cure

Flash: 280°F (138°C) for 3 seconds
Cure: 320°F (160°C) Entire ink film



Pigment Loading



Wilflex™ Additives



Storage

65-90°F (18-32°C)
Avoid direct sunlight
Use within one year of receipt



Clean Up

Ink degradant or press wash



Health & Safety

Find SDS information here: www.avient.com/resources/safety-data-sheets or contact your local CSR



AVIENT
SPECIALTY
INKS

V1.67 (Modified: 04/16/2024)

2024, Avient Corporation. Avient makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Avient makes no warranties or guarantees respecting suitability of either Avient's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. AVIENT MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.