

# P6028 TXP DILUYENTE TRANSPARENTE

# PRINTOP

Printop™ P6028 TXP Diluyente transparente is a plastisol textile additive belonging to the Texiplast™ series. It has been developed to reduce the viscosity of inks, thus allowing the use of high numbering screens.

## HIGHLIGHTS

- /// Does not alter color intensity
- /// Allows working with higher mesh numbers
- /// Low viscosity product

## PRINTING TIPS

- /// 1 Kg -> TXP (Direct Colors), Whites, Bases.  
10- 30 g -> (1-3%) TXP Diluyente Transparente
- /// Use in percentages higher than recommended may cause loss of product properties.












## COMPLIANCE

- /// <https://www.avientspecialtyinks.com/services/compliance-support>

## PRECAUTIONS

- /// The user shall carry out his own tests to determine and check the chemical contents of his prints and the provisions of this Technical Data Sheet before mass production, ensuring that he meets the requirements of his customers with respect to chemical contents.

## RECOMMENDED PARAMETERS

 <b>Fabric Types</b>	 <b>Flash &amp; Cure</b> Flash: Cure:	 <b>Clean Up</b>
 <b>Mesh</b> Count: Tension:	 <b>Pigment Loading</b> N/A	 <b>Health &amp; Safety</b> SDS: Contact your sales representative
 <b>Squeegee</b> Durometer: Profile: Stroke: Angle:	 <b>Additives</b>	<p>2025, Avient Corporation. Avient makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Avient makes no warranties or guarantees respecting suitability of either Avient's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. AVIENT MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.</p>
 <b>Stencil</b> Off Contact: Emulsion Over Mesh:	 <b>Storage</b> Store in a cool, dry place between 18°C to 35°C (65°F to 95°F). 12 months. Keep container closed to prevent drying and/or contamination.	
	AVIENT SPECIALTY INKS	V1.12 (Modified: 16/07/2025)