



FLTRE1064 TRANS WHITE

FLTRE1064 Trans White is a plastisol white with excellent adhesion and wash properties designed for heat transfer using a conventional heat-press with a standard cool/cold-peel application method. This ink offers high opacity, creamy consistency, with excellent printability.

Highlights

-  Ink designed for transfer application
-  Good tensile strength
-  Great cross-linking properties

Printing Tips

-  FLTRE1064 allows transfer to cool for approximately 15 seconds before removing the paper.
-  Consider adjustments to the drying mechanism may be required as the variables of different drying (heat) types, length of dryer conveyor and drying units, will affect the overall transfer finish.
-  Printers should always test the ink on their fabric under their process conditions before printing production runs.

Compliance

-  Non-phthalate
-  Internationally compliant
-  Visit <https://www.avientspecialtyinks.com/services/compliance-support>

Precautions

-  The information above is given in good faith and does not release you from testing inks and fabrics to confirm suitability of substrate and application process to meet your customer standards and specifications.

Recommended Parameters

 Fabric Types Cotton, Cotton/Polyester blends	 Flash & Cure Flash: 220-260°F (105-125°C) Cure: 375°F (190°C)	 Clean Up Unused ink will need to be disposed of responsibly. Standard plastisol cleaners, press wash, or ink degradant
 Mesh Count: 86-125 t/in (34-49 t/cm) Tension: 18n-25n/cm3	 Pigment Loading N/A	 Health & Safety Find SDS information here: www.avient.com/resources/safety-data-sheets or contact your local CSR
 Squeegee Durometer: 70, 60/90/60, 65/95/65 Profile: Square Stroke: 2+ Angle: 10-20%	 Additives K2910 VISCOSITY BUSTER	2025, Avient Corporation. Avient makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Avient makes no warranties or guarantees respecting suitability of either Avient's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. AVIENT MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.
 Stencil 2 on 2 Off Contact: 1/16" (2mm) or greater Emulsion Over Mesh: 15-20%	 Storage 65 -95° F (18 -35° C) Avoid direct sunlight. Use within one year of receipt. Keep container well sealed.	
	AVIENT SPECIALTY INKS	V4.10 (Modified: 10/13/2025)